



## **Device** features

Domestic hot water tank made of ceramicenamelled steel with a single large area spiral coil dedicated to heat pump operation.

The casing is made of a thick layer of hard polyurethane insulation, which ensures long maintenance of the domestic water temperature and thus low operating costs.

For corrosion protection, ceramic enamel was applied using the "wet" method over the entire surface of the exchanger. Tank protection is supported by the use of magnesium anodes. It is also possible to use active titanium anodes, which do not require ongoing maintenance.

## **Specification**

Model			AQT200EC1A R14		
EAN Code			5905567607097		
Tank	Capacity (class)	I	200		
	Colour			White	
	Tank material		Ceramic enamel steel		
	Housing material		Polyurethane foam, artificial leather		
	Maximum pressure bar		10		
	Insulation thickness	mm	42		
	Maximum temperature	°C	80		
	Height	mm	1355		
	Outer diameter	mm	584		
	Net weight	kg	102/116,3		
Integrated electric	Power	kW			
heater	Power supply	V-Hz, Ø			
Magnesium anode	Upper / Bottom	inches/screw	5/4° / - x1		
Heat exchanger	Туре		Single coil		
	Material		Ceramic enamel steel		
	Maximum pressure bar		10		
	Maximum temperature	°C	110		
	Heat pump tank coil surface		2		
	Power (50/10/45°C) kW		17		
	Power (60/10/45°C)		· ·		
	Solar coil surface m²				
	Power (80/10/45°C)	kW			
	Capacity		822		
Hydraulic connections			1"		
	Heat pump output	thread inches thread inches	1"		
	DHW output	thread inches	3/4"		
			3/4"		
	Temppressure valve	thread inches thread inches	3/4		
	Circulation / return	thread inches	3/4"		
	Heater connection	thread inches	6/4"		
	Solar system input	thread inches	U/+		
	Solar system output	thread inches			
	Tank	till ead ilitiles	5		
Warranty					
	Heater and safety valve				
Energy efficiency cla Maintenance	dss				
Static heat loss W		Service and anode exchange obligatory every 18 months			
		82			
Optional accessories / model			AGGE013	AMD33/200A	AMG33/450A
EAN product code			5905567603266	5905567614255	5905567614262
Product name			Electric heater	Magnesium anode - bottom	Magnesium anode - upper
Power kW		kW	3	-	-
Dimmensions mm / inches / screw			6/4"/-	33 × 200 / - / -	33 × 450 / - / -