

Cassette air conditioner

Tenji CC T26Xi ^[R15]

S-LINE

HP-LINE



Unit features



Digital DC
Inverter SKY®



Electrostatic
HD iAIR filter



Wide-angle eMOTO
air supply



Air supply eMOTO
control system



SMART
Wi-Fi



Wired controller
SMART port



SMART LED
panel display ON/
OFF



Wireless remote
control



Wired
controller⁽¹⁾



SMART Follow
mode



Louvre setting
memory



Auto restart
memory



Anti-corrosive
gold fins



Drip tray
heater



Compressor
crankcase heater



Timer



Cooling at low
outdoor temp.
down to -15°C



Heating at low
outdoor temp.
down to -22°C



Self-diagnostics



Sleep mode



Automatic 4D
louvres



Integrated
condensate pump



Fresh air
supply⁽¹⁾



ON/OFF remote
output



Alarm
output



Weekly controller
output



Central controller
output



360°
air supply



Individual louvre
control



BMS
Modbus⁽¹⁾



BMS
Bacnet⁽¹⁾

Technical specification

Model				Tenji 2,6 kW
Capacity	Cooling	Nom. (Min. - Max.)	W	2638
Rated input		Nom. (Min. - Max.)	W	-
Operating current		Nom. (Min. - Max.)	A	-
Capacity	Heating	Nom. (Min. - Max.)	W	2931
Rated input		Nom. (Min. - Max.)	W	-
Operating current		Nom. (Min. - Max.)	A	-
Reversible heat pump type				air-to-air
Design load in cooling mode			kW	-
SEER			W/W	-
Energy efficiency class, cooling				-
Annual electric energy consumption, cooling			kWh/a	-
Design load in heating mode (Tbiv -7°C)			kW	-
SCOP			W/W	-
Energy efficiency class, heating				-
Annual electric energy consumption, heating			kWh/a	-
Dehumidification			l/h	-
Maximum energy consumption			W	-
Maximum operating current			A	-
Indoor unit				T26Xi R15
EAN product code				5905567606267
Fan speed		T / H / M / L	rpm	840 / 770 / 730 / 680
Air flow		T / H / M / L	m³/h	610 / 500 / 415 / 320
Sound pressure level		T / H / M / L	dB(A)	41 / 37 / 30,5 / 24,5
Sound power level			dB(A)	55
Rated input			W	40
Operating current			A	0,2
Net dimensions		W × D × H	mm	570 × 570 × 245
Gross dimensions		W × D × H	mm	715 × 640 × 295
Net weight / Gross weight			kg	16,1 / 18,8
Condensate drain			mm	25
Panel	Model			TCCX2p [R15]
	EAN product code			5905567606243
	Net weight	W × D × H	mm	620 × 620 × 50
	Gross weight	W × D × H	mm	715 × 700 × 115
	Net weight / Gross weight		kg	2,7 / 4,3
Outdoor unit				-
EAN product code				-
Fan speed		H / M / L	rpm	-
Maximum air flow			m³/h	-
Sound pressure level			dB(A)	-
Sound power level			dB(A)	-
Net dimensions		W × D × H	mm	-
Gross dimensions		W × D × H	mm	-
Bracket spacing		W × D	(mm)	-
Net weight / Gross weight			kg	-
Refrigerant	Type			-
	GWP			-
	≤ 5m	kg		-
		TCO ₂ eq		-
	Charged (> 5m)		g/mb	
Pipe connections		Liquid/Gas	mm (inches)	Φ6,35 / Φ9,52 (1/4" / 3/8")
Maximum installation length			m	-
Maximum height difference			m	-
Compressor type				-
Type of outdoor unit power supply			V-Hz, Ø	220-240-50, 1f
Electrical protection			A	-
Power cables: outdoor unit			pcs × mm²	Look data at HIRO
Control and power cables: indoor unit - outdoor unit			pcs × mm²	4 × 1
Indoor operating range (Cooling / Heating)			°C	16~32 / 0~30
Outdoor operating range (Cooling / Heating)			°C	-
Compatible systems				
1:1 SINGLE				
1:2 DUAL				
1:X MULTI S-Line				●
1:X MULTI N-Line				
1:X MULTI HP-Line				●

H - High; M - Middle; L - Low; S - Silent