

Wall-mounted air conditioner

Teta Mirror TM26X^[R16]



Unit features

Digital DC Inverter SKY®	Automatic cleaning iAIR	Automatic purification iClean ⁽¹⁾	Super Ionizer iAIR	UV lamp	3-in-1 (Ca + Si.Ion + Vit.C) iAIR filter ^(*)	3-in-1 (Photo. + Act.Carb. + Nano) iAIR filter ^(**)	Electrostatic HD iAIR filter
Super Silent eMOTO mode	Automatic 4D louvres	Windless eMOTO air supply	Turbo eMOTO mode	Air supply eMOTO control system	Eco eMOTO mode	Wide-angle eMOTO air supply	SMART Wi-Fi
SMART panel display ON/OFF	SMART Follow mode ⁽¹⁾	Wireless remote control	SMART heating to 8°C ⁽¹⁾	Louvre setting memory	Auto restart memory	Anti-corrosive gold fins	Drip tray heater
Compressor winding heating ⁽¹⁾	Timer	Cooling at low outdoor temp. down to -15°C	Heating at low outdoor temp. down to -25°C ⁽¹⁾	Double-sided condensate drainage	Self-diagnostics	Sleep mode	Energy optimization ⁽¹⁾

1

1. Feature not available in Multi Split system

* 3-in-1 iAIR filter: Catechin + Silver Ion + Vitamin C

** 3-in-1 iAIR filter: Photocatalytic + Activated carbon + Cold Nano

Technical specification

Model				Teta Mirror 2,6 kw
Capacity	Cooling	Nom. (Min. - Max.)	W	2610 (940-3700)
Rated input		Nom. (Min. - Max.)	W	699 (240-1380)
Operating current		Nom. (Min. - Max.)	A	3,0 (1,0-6,0)
Capacity	Heating	Nom. (Min. - Max.)	W	3000 (940-4000)
Rated input		Nom. (Min. - Max.)	W	740 (240-1552)
Operating current		Nom. (Min. - Max.)	A	3,2 (1,0-6,7)
Reversible heat pump type				air-to-air
Design load in cooling mode			kW	2,6
SEER			W/W	8,5
Energy efficiency class, cooling				A+++
Annual electric energy consumption, cooling			kWh/a	108
Design load in heating mode (Tbiv -7°C)			kW	2,4
SCOP			W/W	4,6
Energy efficiency class, heating				A++
Annual electric energy consumption, heating			kWh/a	731
Dehumidification			l/h	1,0
Maximum energy consumption			W	1552
Maximum operating current			A	6,7
Indoor unit				TM26Xi R16
EAN product code				5905567606496
Fan speed	T / H / M / L / ML / S	rpm	1250 / 1080 / 920 / 800 / 700 / 650	
Air flow	T / H / M / L / ML / S	m³/h	560 / 480 / 410 / 360 / 310 / 275	
Sound pressure level	T / H / M / L / ML / S	dB(A)	42 / 38 / 33 / 27 / 21 / 18	
Sound power level		dB(A)	52	
Rated input		W	25	
Operating current		A	0,1	
Net dimensions	W × D × H	mm	790 × 192 × 275	
Gross dimensions	W × D × H	mm	860 × 265 × 345	
Net weight / Gross weight		kg	8,5 / 10,5	
Condensate drain		mm	16	
Outdoor unit				TO26Xo R16
EAN product code				5905567606502
Fan speed	T / H / M / L / S	rpm	900 / 810 / 730 / 610 / 450	
Maximum air flow		m³/h	2200	
Sound pressure level		dB(A)	51	
Sound power level		dB(A)	61	
Net dimensions	W × D × H	mm	795 × 305 × 551	
Gross dimensions	W × D × H	mm	835 × 328 × 575	
Bracket spacing	W × D	(mm)	434 × 278	
Net weight / Gross weight		kg	23 / 25	
Refrigerant	Type		R32	
	GWP		675	
	≤ 5m	kg	0,45	
		TCO ₂ eq	0,304	
	Charged (> 5m)	g/mb	15	
Pipe connections	Liquid/Gas	mm (inches)	Φ6,35 / Φ9,52 (1/4" / 3/8")	
Maximum installation length		m	25	
Maximum height difference		m	10	
Compressor type				Rotary DC
Type of outdoor unit power supply		V-Hz, Ø	220-240-50, 1f	
Electrical protection		A	C10	
Power cables: outdoor unit		pcs × mm²	3 × 1,5	
Control and power cables: indoor unit - outdoor unit		pcs × mm²	5 × 1,5	
Control and power cables: hiro unit - indoor unit		pcs × mm²	4 × 1	
Indoor operating range (Cooling / Heating)		°C	16~32 / 0~30	
Outdoor operating range (Cooling / Heating)		°C	-15~53 / -25~30	
Compatible systems				
1:1 SINGLE				●
1:2 DUAL				
1:X MULTI S-Line				
1:X MULTI N-Line				●
1:X MULTI HP-Line				

T - Turbo; H - High; M - Medium; L - Low; S - Silent;