


Wall-mounted air conditioner

Versu Cloth Stone VCS35X ^[R15]

S-LINE

HP-LINE



Unit features



Digital DC Inverter SKY[®]



Textile changeable front panel



Automatic purification iClean ⁽¹⁾



Super Ionizer iAIR



3-in-1 (Si, Ion + Photocat. + Nano) iAIR filter ⁽¹⁾



Antibacterial HEPA iAIR filter



Electrostatic HD iAIR filter



Super Silent eMOTO mode ⁽¹⁾



Automatic 4D louvres



Rotating louvre 180°



Turbo eMOTO mode ⁽¹⁾



Upwards cascade air supply



Downwards cascade air supply



Air supply eMOTO control system



Eco eMOTO mode ⁽¹⁾



Wide-angle eMOTO air supply



Humidity sensor ⁽¹⁾⁽³⁾



SMART Wi-Fi



Wired controller SMART port ⁽²⁾



SMART panel display ON/OFF



SMART Follow mode



Wireless remote control



Wired controller ⁽²⁾



SMART heating to 8°C ⁽¹⁾



Louvre setting memory



1W standby mode ⁽¹⁾



Auto restart memory



Anti-corrosive gold fins



Drip tray heater



Compressor crankcase heater



Silence mode



Timer



Cooling at low outdoor temp. down to -15°C



Heating at low outdoor temp. down to -22°C ⁽¹⁾



Double-sided condensate drainage



Self-diagnostics



Sleep mode



BMS Modbus ⁽²⁾



BMS Bacnet ⁽²⁾

Technical specification

Model				Versu Cloth Stone 3,5 kW	
Capacity	Cooling	Nom. (Min. - Max.)	W	3516 (1320-4307)	
Rated input		Nom. (Min. - Max.)	W	900 (130-1650)	
Operating current		Nom. (Min. - Max.)	A	3,9 (0,6-7,2)	
Capacity	Heating	Nom. (Min. - Max.)	W	3809 (879-4395)	
Rated input		Nom. (Min. - Max.)	W	950 (120-1500)	
Operating current		Nom. (Min. - Max.)	A	4,1 (0,5-6,5)	
Reversible heat pump type				air-to-air	
Design load in cooling mode			kW	3,5	
SEER			W/W	8,5	
Energy efficiency class, cooling				A+++	
Annual electric energy consumption, cooling			kWh/a	146	
Design load in heating mode (Tbiv -7°C)			kW	2,5	
SCOP			W/W	4,6	
Energy efficiency class, heating				A++	
Annual electric energy consumption, heating			kWh/a	776	
Dehumidification			l/h	1,2	
Maximum energy consumption			W	2200	
Maximum operating current			A	9,6	
Indoor unit				VCS35Xi R15	
EAN product code				5905567601088	
Fan speed		T / H / M / L / ML / S	rpm	1122 / 910 / 823 / 710 / 652 / 600	
Air flow		T / H / M / L / ML / S	m³/h	700 / 555 / 445 / 380 / 270 / 230	
Sound pressure level		T / H / M / L / ML / S	dB(A)	40 / 32 / 27 / 24 / 21 / 19	
Sound power level			dB(A)	53	
Rated input			W	13	
Operating current			A	0,1	
Net dimensions		W × D × H	mm	920 × 211 × 321	
Gross dimensions		W × D × H	mm	1005 × 295 × 385	
Net weight / Gross weight			kg	11,3 / 14,2	
Condensate drain			mm	16	
Outdoor unit				VO35Xo R15	
EAN product code				5905567606663	
Fan speed		H / M / L	rpm	800 / 620 / 450	
Maximum air flow			m³/h	2200	
Sound pressure level			dB(A)	53	
Sound power level			dB(A)	62	
Net dimensions		W × D × H	mm	765 × 303 × 555	
Gross dimensions		W × D × H	mm	887 × 337 × 610	
Bracket spacing		W × D	(mm)	452 × 286	
Net weight / Gross weight			kg	26,4 / 28,8	
Refrigerant	Type			R32	
	GWP			675	
	≤ 5m	kg		0,7	
		TCO ₂ eq		0,47	
	Charged > 5m	g/mb		12	
Pipe connections		Liquid/Gas	mm (inches)	Φ6,35 / Φ9,52 (1/4" / 3/8")	
Maximum installation length			m	25	
Maximum height difference			m	10	
Compressor type				Rotary DC	
Type of outdoor unit power supply			V-Hz, Ø	220-240-50, 1f	
Electrical protection			A	C10	
Power cables: outdoor unit			pcs × mm²	3 × 1,5	
Control and power cables: indoor unit - outdoor unit			pcs × mm²	5 × 1,5	
Control and power cables: hiro unit - indoor unit			pcs × mm²	4 × 1,5	
Indoor operating range (cooling / heating)			°C	16-32 / 0-30	
Outdoor operating range (cooling / heating)			°C	-15-50 / -22-30	
Compatible systems					
1:1 SINGLE				●	
1:2 DUAL					
1:X MULTI S-Line				●	
1:X MULTI N-Line					
1:X MULTI HP-Line				●	

T - Turbo; H - High; M - Medium; L - Low; ML - Medium-Low; S - Silent;